

BOSCH Electronic Highflow Gas Continuous Flow – E Models

Technical Information

BOSCH E UNITS	Bosch 17E	Bosch 21E	Bosch 26E
No. of bathrooms	1	1-2	2-3
Installation	External	External	External
Ignition	Electronic	Electronic	Electronic
L/min (25°C rise)	17	21	26
Min. operating inlet water pressure (kPa)	100	100	100
Min. constant water pressure for Max. flow (kPa)	100	130	230
Max. inlet water pressure (kPa)	1000	1000	1000
Mj/H	135	170	200
Star Rating	6.30	6.30	5.53
Antifrost	Standard	Standard	Standard
Transfer valve required for solar	No	No	No
50°C Limited Part Number	YS1770RA5*	YS2170RA5*	YS2670RA5*
Gas Type	NG/LPG	NG/LPG	NG/LPG
Electrical Supply	230 VAC - 240V 50 Hz (10amp weatherproof power point required within 500 mm of the unit)	230 VAC - 240V 50 Hz (10amp weatherproof power point required within 500 mm of the unit)	230 VAC - 240V 50 Hz (10amp weatherproof power point required within 500 mm of the unit)
Temperature Controllers	Up to 4 temperature controllers can be installed	Up to 4 temperature controllers can be installed	Up to 4 temperature controllers can be installed
Dimensions			
Unit Height (mm)	520	520	600
Unit Width (mm)	350	350	350
Unit Depth (mm)	170	170	170
Carton Weight (Kg)	18	19	22
Domestic Warranty			
Parts and Labour	3 Years		
Heat Exchanger (part only)	10 Years		

Mackie Plumbing and Gas Pty Ltd
PO Box 1493, South Perth, 6915, Western Australia
Tel: 1800 MACKIE (622 543)
Email: reception@mackieplumbingperth.com.au

Registered in Australia: ABN: 29 168 696 204
Plumbing & Gas Licence: PL8621 / GS015660

