

STIEBEL ELTRON SIMPLE X

Technical Information

Model number	SIMPLEX
Rated output (415V)	13.2kW
Rated current (415V)	20 Amp
Phases	3/PE
Electrical installation	As per AS/NZS3000
Installation requirements	AS/NZS3500.4.2 & local requirements
Switch on flow rate	4.5 L/min = 41°C temperature rise
Permissible operating pressure	1000 kPa
Temperature adjustment	N/A
IP Rating	IP24
Height	210mm
Width	360mm
Depth	125mm
Colour	white
Nominal capacity	0.5L
Flow rate limiter (if fitted) L/min	7.5 Max = 25°C temperature rise
Approvals	WaterMark Lic No. WMKA21273. AS3498
Heating system	Copper Tubular
Domestic Warranty*	2 years

MPG RECOMMENDATION – UPGRADE TO DHB-13E

Wilson Simple X	DHB-13E
2 year warranty	5 year warranty
4.5L per minute flow rate. If less than 4.5L of hot water are used per minute the unit will switch off. A common complaint from customers is that water temperatures fluctuate.	3L per min flow rate Better flow rate per minute, only three (3) litres of water use per minute required for unit to engage.

If you would like to see a DHB-13 in operation in a showroom or to get a free quote please call **1800 MACKIE (1800 622 543)**

Mackie Plumbing and Gas Pty Ltd
PO Box 1493, South Perth, 6915, Western Australia
Tel: 1800 MACKIE (622 543)
Email: reception@mackieplumbingperth.com.au

Registered in Australia: ABN: 29 168 696 204
Plumbing & Gas Licence: PL8621 / GS015660

