

Technical Information

	Thermann 16	Thermann 20	Thermann 26
Selecting the right unit for you...	1 bathroom	2 bathrooms	2-3 bathrooms
Energy Rating (Stars 50C)	6.3	6.5	6.1
Energy Rating (Stars 60C)	6.0	6.0	6.0
Capacity (At 25°C Rise):	16 ltr/min	20 ltr/min	26 ltr/min
Capacity (At 40°C Rise):	10 ltr/min	12.5 ltr/min	16.25 ltr/min
Gas Connection:	R3/4" (20mm)	R3/4" (20mm)	R3/4" (20mm)
Gas Consumption:	125 mj/h	158 mj/h	200 mj/h
Gas Type:	NG, LPG	NG, LPG	NG, LPG
Relief Valve Setting:	1400 kpa	1400 kpa	1400 kpa
Star Rating:	6.0 star	6.0 star	6.0 star
Temperature Setting:	50 OR 60 deg c	50 OR 60 deg c	50 OR 60 deg c
NOTE: 60 deg c unless specifically requested			
Water Connections:	R3/4" (20mm)	R3/4" (20mm)	R3/4" (20mm)
Dimensions	Height: 520 mm Width: 350 mm Depth: 200 mm Weight (Dry): 15 kg	Height: 520 mm Width: 350 mm Depth: 200 mm Weight (Dry): 15 kg	Height: 520 mm Width: 350 mm Depth: 200 mm Weight (Dry): 15 kg
Warranty	Spare Parts And Labour: 3 years Heat Exchanger Warranty: 12 years	Spare Parts And Labour: 3 years Heat Exchanger Warranty: 12 years	Spare Parts And Labour: 3 years Heat Exchanger Warranty: 12 years

Controller

Kitchen Controller with 15m cable
Bathroom Controller with 15m cable
Ensuite Controller with 15m cable

User Manual

Opens PDF